MODELS: Douglas Dolphin 8, 7 PCAmM

```
T.C. NUMBER: 2-492
     Engines
                                        2 P&W Wasps S3D1
                                        Maximum, except takeoff
28.5 in. Hg., 2100 rpm (450 hp)
Takeoff (one minute)
     Placard limits
                                        30.0 in. Hg., 2100 rpm (450 hp) Glide or dive - 170 mph Ind. Plaps extended - 100 mph Ind.
     Placard speeds
     Placard ceiling
                                        2000 ft. (density altitude) either engine inoperative
                                        302 gallons (6 tanks in CS wing; 2 main 96 gallons
                                           each; 2 auxiliary outboard 30 gallons each; 2 auxiliary outboard 30 gallons each; 2 auxiliary inboard 25 gallons each)
                                        20 gallons
     Oil
     No. passengers
     Baggage
                                        132 lbs. (single compartment aft of cabin)
     Standard weight
                                        9500 lbs.
                                        (+30.0) and (+40.2)
Aero. Bulletin 7A, Section 3
1280 and up manufactured prior to July 1, 1940
eligible. Approval expired as of that date.
     C.G. limits
     Spec. basis
     Serial Nos.
     EQUIPMENT:
           (Datum is leading edge of center section wing at side of fuselage.)
     Class I:
           101. Two engine ring cowls
                                                                            36 lbs.
           102. Battery - 12V
103. Starters (electric)
                                                                            65 lbs.
                  Generator - 50 amp
                                                                            34 lbs.
           104.
           105.
                  36x8 wheels and brakes (Bendix) with
                   40x10 9-ply tires (wheels must be
           placarded for these tires)
106. Two wing floats and struts
107. Pressure fire extinguisher system
                                                                          213 lbs.
                                                                            39 lbs.
                                                                            27 lbs.
                  Landing lights
                                                                             2 lbs.
           109.
                  Sea anchor and 150 ft. rope
                                                                           20 lbs.
           110. Boat hook
111. 8-1/4x4 retractable tail wheel with
                                                                             2 lbs.
                  solid rubber tire
           112. Wings equipped with T.E. full flaps
                  manually oildraulic operated and drooping type ailerons
           113. Elevator control surface equipped with
                  manually operated T.E. tabs
                                                                            15 lbs.
           114.
                  Tool kit
           115. Hoist sling
                                                                             7 lbs.
                                                                             7 lbs.
           116. Bilge pump
           117. Toilet equipment
                                                                           18 lbs.
           118. Water container and 1-1/2 gallons water
                                                                            14 lbs.
                                                                          135 lbs.
           119. Radio complete with 2 receivers
           120. Propellers - controllable metal (Hamilton Standard, hubs 8460, blades 6101-10; low pitch setting 15 degrees)
```

- NOTE 1. Eligible for export to all countries except Great Pritain, Canada and Australia (2/28/37).
- NOTE 3. Same as Model 8-114 (2-483), Model 11 (2-479), Model 12 (2-486) and Model 129 (2-487) except for changes in engines, propellers, cabin interior arrangements and items of equipment.